

### AMENDMENT TO THE SPECIFICATION

Please amend paragraph [0019] in the publication as follows:

Referring to both FIGS. 2-1 and 2-2, cable 224 includes a main electrical ~~connector~~ conductor 221, a first electrical ~~connector-conductor~~ 229 and a second electrical ~~connector~~ conductor 235. Those skilled in the art will recognized that multiple electrical ~~connectors~~ conductors can be housed in cable 224 to electrically connect to a clamp, such as clamp 200.

Please amend paragraph [0020] in the publication as follows:

The main electrical ~~connector-conductor~~ 221 is capable of carrying a high current such that the high current can charge a battery. Terminal 218 is electrically coupled to the main electrical ~~connector-conductor~~ 221. Terminal 218 includes terminal hole 220 which aligns with first hole (not shown in FIGS. 2-1 or 2-2) of first hand grip 210. Removable fastener 222 (shown fastened in FIG. 2-1 and shown unfastened in FIG. 2-2) couples terminal 218 to first hand grip 210 through the first hole and terminal hole 220 such that fastener 222 can disconnect clamp 200 from cable 224.

Please amend paragraph [0021] in the publication as follows:

~~First electrical conductor 229 includes first portion 230 and second portion 232. Second electrical conductor 235 includes first portion 231 and second portion 233. First portion~~ Clamp 200 includes a first wire connector 230 of first electrical conductor 229 that is electrically coupled to conductive piece 236 at one end and coupled to a first electrical plug 226 at the other end. Clamp 200 also includes a second wire connector ~~First portion 231 of second electrical conductor 235 that is electrically coupled to second jaw 208 through rivet 234 at one end and coupled to first electrical plug 226 at the other end. Second portions 232 and 233 are coupled to cable 224 at one end and coupled to second electrical plug 228 at the other end. First and second electrical~~

conductors 229 and 235 of cable 224 are electrically coupled to a second electrical plug 228.

First electrical plug 226 is removably electrically connected with second electrical plug 228.